


REV. LTR.	DESCRIPTION	APPROVAL	DATE
A2	Update drawing	W. Q. LI	2024. 08. 08

Specifications:

1. Voltage rating:250V AC/DC.
2. Current rating:5. 0A AC/DC.
3. Withstanding voltage:1500V AC/minute.
4. Ambient temperature range:-25 ~ +85℃.
5. Insulation resistance: ≥1000MΩ.
6. Contact resistance: ≤. 20mΩ.
7. Applicable wire Sizes:AWG#18 ~ #28.
8. Housing①:PA66 UL94V-0/Natural.
9. Upper terminal②:Brass/Tin Plating.



Outside drawing

Product material No:

EN420MSWC-*** * **

NO OF Poles

Terminal Plating

B=Bright-Tin

M=Mist-Tin

G=Gold flash

Plastic Material

P=PA66

T=PA9T

L=LCP

Packing

T=Tube

B=Bag

R=Tape&Reel

Plastic Color

Y=Faint Yellow

R=Red




B=Black

W=White

Pin number:

Poles	DIM A	DIM B	Poles	DIM A	DIM B
2X1P		5. 40	2X8P	29. 40	34. 80
2X2P	4. 20	9. 60	2X9P	33. 60	39. 00
2X3P	8. 40	13. 80	2X10P	37. 80	43. 20
2X4P	12. 60	18. 00	2X11P	42. 00	47. 40
2X5P	16. 80	22. 20	2X12P	46. 20	51. 60
2X6P	21. 00	26. 40			
2X7P	25. 20	30. 60			

SECTION A-A
SCALE 1:1



Recommended P. C. B Layout
General Tolerance ± 0. 05



http://www.euvchn.com		EUV ® EUV ELECTRONICS CO., LTD 兆進電子有限公司			
30~Above ± 0. 30	ANGLE: ∠ ± 1°	TITLE	4. 20mm Connectors (90° DIP)		
10~30 ± 0. 20	SCALE:1:1	PART NO.	EN420MSWC-***-***-		
5~10 ± 0. 15	SHEET:1 OF 1	APPROVAL	CHECK	DRAWN	DATE
0~5 ± 0. 10	PROJECT	W. Q. LI	X. H. LIN	K. J. ZENG	2024. 08. 08
TOLERANCES ARE (UNIT:mm)		SIZE:A4			